

DURATA INLINE 34-840-3000LM FL 3000lm



Technical Details:

Luminous Flux:	3400 lm
LED Output:	33 W
Light Yield:	100 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<2
Beam Angle:	100 °
Unified Glare Rating (UGR):	<22
Light Emission:	downward
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Input Current:	AC 220-240V, 50/60Hz
Power Consumption:	34 W
Contains Driver:	✓
Driver Manufacturer:	Boke
Power Factor (PF):	>0.95
Input Driver:	plug connector
Output of Driver:	DC 38V, 900mA
CC/CV:	CC
Input Lamp:	cable with flying leads
Switching Cycles:	>100.000
Electrical Protection Class:	I
Ambient Temperature (TA):	-10°C - 40°C
Storage Temperature:	-20°C - 55°C

Dimensions:	1260x64x47 mm
Installation Depth:	64 mm
Mounting:	Decke
Montageart:	recessed
IP Class:	20
IK Code:	07
Housing Color	white
Housing Material:	aluminum
Coating:	powder-coated
Cover:	opal
Net Weight:	1971 g
Type of Packaging:	box
Dimensions of Packaging:	1316*95*95
Weight incl. Packaging:	2.218 kg
Content Master Package:	12
Dimensions of Master Package:	1336*405*310 mm
Weight Master Package:	29,14 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L90/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405 11 90 90
Certifications	CE
Barcode:	4250557824680
Elegante, Deckeneinbau-Lichtlinienleuchte	
optional auch dimmbare Treiber erhältlich	
optional 5 unterschiedliche LED-Optiken lieferbar	

Information and Downloads:



