

Order number: LG56220

Fenestra Value Rectangle MKIII 12518 33-840-3600LM, 120lm/W, UGR19 BAP RAL9003



Technical Details:

Luminous Flux:	4287 lm
LED Output:	35 W
Light Yield:	122 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	110 °
Unified Glare Rating (UGR):	<21
Light Emission:	downward
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Input Current:	AC 220-240V, 50/60Hz
Power Consumption:	35 W
Contains Driver:	✓
Driver Manufacturer:	Lifud
Power Factor (PF):	>0.96
Input Driver:	terminal
Output of Driver:	DC 30 - 42V, 900mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>50.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 45°C
Storage Temperature:	-40°C - 50°C

Dimensions:	1246x184x12 mm
Mounting:	Decke
IP Class:	66
IK Code:	04
Housing Color	white
Housing Color (RAL Code):	similar 9003
Housing Material:	aluminum
Coating:	lacquered
Cover:	opal
Net Weight:	2159 g
Type of Packaging:	box
Weight incl. Packaging:	2.607 kg
Content Master Package:	4
Dimensions of Master Package:	180x284x1283 mm
Weight Master Package:	11,23 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE,TÜV,GS,ENEC
Barcode:	4250557823461

Information and Downloads:

