

# Modulux BATWING Linear LED- Modul 150-45/60-940-9600lm-WH DALI2



## Product information "Modulux BATWING Linear LED- Modul 150-45/60-940-9600lm-WH DALI2"

Linear LED tracklight for 3-phase trackrails with Dali dimming driver

Elegant, flat LED luminaire with integrated 3-phase track adapter which is completely integrated in the standard track rails. Elegant, ultra flat appearance only 12mm high and 100mm wide. Special LED Lenspanel with 20° x 90° beamangle. The wings are adjustable by 30° each. Ideal for illuminating supermarket shelves, retail areas, exhibition halls, extremely high luminous flux up to 9600 lumens with only 60W consumption corresponding to up to 160 lumens / watt.

- Easy and fast installation using 3-phase trackrail adapters for 4 to 6 wires Dali rails
- 3 selectable power phases, compatible with all common track systems
- Adjustment output power: Adjustable LED driver 45, 50, 55, 60Watt
- Dali 2 LED driver with integrated design
- Modular structure of the lens panel
- The individual modules can be seamlessly lined up. It creates the impression of a continuous line of light.
- Good heat dissipation and optimal light distribution
- Available in 2 housing colors: black, white optional also in silver



### Technical Details:

Luminous Flux	9600 lm
Light Yield:	160 lm/W
Light Temperature:	4000 K
Color Rendering Index (CRI)	≥90 Ra
Color Consistency (SDCM):	3
Power Consumption:	45, 50, 55, 60 W
Power Factor (PF):	0.95
Operating Hours:	>70.000 h L80/B20
Switching Cycles:	>100.000
Ignition Time:	<0,5 s
Ambient Temperature (TA):	-25°C - 50°C
Housing Material:	steel
Housing Color	white
Coating:	powder-coated
Dimensions	1492x100x12 mm
Net Weight:	1800 g
Warranty	5 years

Information and Downloads:



5000K, 6000K

- available in two lengths: 60cm and 150cm