


# Modulux BATWING Linear LED- Modul 150-45/60-940-10200lm-WH DALI2



3-phases Stromschiene

## Technical Details:

Luminous Flux:	10200 lm
LED Output:	60 W
Light Yield:	170 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥90 Ra
Color Consistency (SDCM):	<3
Unified Glare Rating (UGR):	<25
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	DALI,Push-Dim
LED-Chip Manufacturer:	EBRIGHT
LED-Chip:	SMD 2835
Number of LED:	240
Ignition Time:	<0,5 s
Input Current:	AC 220 - 240V, 259-340mA, 50/60Hz
Power Consumption:	Power Select (45, 50, 55, 60 W)
Contains Driver:	✓
Driver Manufacturer:	Litegear
Power Factor (PF):	>0.95
Input Driver:	lighting track
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	Power rail
Switching Cycles:	>100.000
Electrical Protection Class:	I
Compatible with Emergency Current:	✓

Dimensions:	1492x100x12 mm
Mounting:	Decke,Stromschiene
IP Class:	20
IK Code:	03
Housing Color	white
Housing Color (RAL Code):	similar 9016
Housing Material:	steel
Coating:	powder-coated
Special Feature of Housing:	3-Phase adapter
Cover:	Lens
Net Weight:	1800 g
Type of Packaging:	none
Weight incl. Packaging:	2.1 kg
Content Master Package:	10
Dimensions of Master Package:	1570x390x290 mm
Weight Master Package:	21 kg
Product Line:	Premio Line
Warranty	5 years
Operating Hours:	70.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,TÜV
spezielle Optik für Supermarktregale	
special optics for shelf lighting in supermarkets	
2 x 90° x 20° double asymmetric 30° adjustable til	
Power adjust: 45/50/55/60W 9600LM max. 160lm/W	

Storage Temperature:

-40°C - 85°C

Information and Downloads:

