

# SATURNA PRO HighBay 100-200-840-40000LM DALI D4i Dim UGR20-25 BEG 200lm/W Zhaga Book 18 Adapter



## Technical Details:

Luminous Flux:	40000 lm
LED Output:	200 W
Light Yield:	205 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<5
Beam Angle:	90 °
Unified Glare Rating (UGR):	<22
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	0-10V,DALI,Push-Dim
LED-Chip Manufacturer:	Liteon
LED-Chip:	SMD 5050
Number of LED:	400
Ignition Time:	<0,5 s
Input Current:	AC 100-277V, 0,25-1mA, 50/60Hz
Power Consumption:	Power Select (100,120, 140,160,180,200 W)
Contains Driver:	✓
Power Factor (PF):	>0.96
Input Driver:	cable with flying leads
Output of Driver:	DC 140-260V
CC/CV:	CC
Output Current Adjustable:	✓

Dimensions:	390x134 mm
Mounting:	Decke
Montageart:	surface mounted
IP Class:	66
IK Code:	10
Housing Color	grey
Housing Color (RAL Code):	similar 9006
Housing Material:	Aluminium ADC12 +PC Linse
Coating:	powder-coated
Special Feature of Housing:	Zhaga Book 18 Sockel
Cover:	Lens
Net Weight:	3550 g
Type of Packaging:	box
Dimensions of Packaging:	410x410x150
Weight incl. Packaging:	4.37 kg
Content Master Package:	1
Dimensions of Master Package:	410x420x160 mm
Weight Master Package:	4,37 kg
Product Line:	Premio Line
Warranty	5 years
Operating Hours:	100.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE,LM80
Barcode:	4250557827575

Switching Cycles:	>100.000
Electrical Protection Class:	I
Ambient Temperature (TA):	-40°C - 55°C
Storage Temperature:	-40°C - 70°C

TGIC Beschichtung/Coating, RG1, THD<15%

UGR <19 mit 60° Linse, 205lm/W max @100W

Dali 2 DIM 12V DC Ausgang für Sensor Zhaga Book 18

Dustfree design , D4i Dali Data Output

Information and Downloads:

