


Kompakter DALI-2 Treiber inkl. Zugentlastung



Technical Details:

Dimmable:	✓
Method of Dimming:	DALI, Push-Dim, DALI-2
Input Current:	AC 198-264V, 150mA, 50/60Hz, DC 180-280V
Power Consumption:	24 W
Driver Manufacturer:	KGP
Power Factor (PF):	>0.94
Input Driver:	terminal
Output of Driver:	DC 3-45V, 100-800mA
CC/CV:	CC
Output Current Adjustable:	✓
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 50°C
Storage Temperature:	-20°C - 90°C

Cut-Out Dimensions:	21 mm
Montageart:	surface mounted
IP Class:	20
Housing Color	white
Housing Material:	plastic
Special Feature of Housing:	Selectable output current
Net Weight:	50 g
Type of Packaging:	none
Weight incl. Packaging:	0.055 kg
Content Master Package:	144
Dimensions of Master Package:	315x255x150 mm
Weight Master Package:	7,92 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	75.000 h TC<85°C
Disposal Obligation:	✓
Customs Tariff Number:	8504408390
Certifications	CE, TÜV, ENEC, SELV

Information and Downloads:

