

LYONA 335-20/827-840-2500LM CCT-/Power Select max. 125lm/W



Product information "LYONA 335-20/827-840-2500LM CCT-/Power Select max. 125lm/W"

Universal surface-mounted luminaire with universal installation base

Lyona is a universal wall/ceiling surface-mounted luminaire with color temperature selection: CCT Select 2700/3000/4000K and Power Select: 8, 10.5, 14, or 20W, corresponding to a luminous flux of 900, 1200, 1700, and 2500 lumens.

Lyona has an impressiv service-friendly, modular design; all luminaires are based on a modular installation base. The luminaire can be mounted on walls and ceilings or, using optional spring clamps, partially recessed into the ceiling.

- Optional version with smart wireless motion sensor available. Swarm function possible with switchable orientation lighting.

- Ideal for stairwells or hallways. The sensor operates in up to two axes vertically in stairwells and additionally in a horizontal axis, for example, in hallways.

Several Lyona luminaires will network together over 2,4GHz signal.

- Optional version with battery-powered emergency lighting available; automatic self-test

- Also available as a DALI version


- Housing made of impact-resistant polycarbonate IK10

- Weatherproof design: IP65 for outdoor installation under canopies or in bathrooms

Number of lights on a 16B circuit breaker: 42

Areas of application:

Stairwells, hotels/offices, sanitary facilities, hallways/rooms, basements/storage rooms, outdoors under canopies



Technical Details:

Luminous Flux	2500 lm
Light Yield:	125 lm/W
Light Temperature:	2700, 3000, 4000 K
Color Rendering Index (CRI)	≥80 Ra
Color Consistency (SDCM):	3
Power Consumption:	8, 10.5, 14, 20 W
Power Factor (PF):	0.95
Operating Hours:	>100.000 h L80/B50
Switching Cycles:	>100.000
Ignition Time:	<0,5 s
Ambient Temperature (TA):	-40°C - 50°C
Housing Material:	Polycarbonat
Housing Color	white
Dimensions	335x69 mm
Cut-Out Dimensions	310 mm
Net Weight:	1180 g
Warranty	5 years

Information and Downloads:

