


LYONA 400-32/827-840-4000LM CCT-/Power Select DALI D4i Dim



Product information "LYONA 400-32/827-840-4000LM CCT-/Power Select DALI D4i Dim"

Universal surface-mounted luminaire with universal installation base

Lyona is a universal wall/ceiling surface-mounted luminaire with color temperature selection: CCT Select 2700/3000/4000K and Power Select: 12, 17, 23 or 32W, corresponding to a luminous flux of 1400, 2000, 3000 and 4000 lumens.

Lyona has an impressiv service-friendly, modular design; all luminaires are based on a modular installation base. The luminaire can be mounted on walls and ceilings or, using optional spring clamps, partially recessed into the ceiling.

- Optional version with smart wireless motion sensor available. Swarm function possible with switchable orientation lighting.
- Ideal for stairwells or hallways. The sensor operates in up to two axes vertically in stairwells and additionally in a horizontal axis, for example, in hallways.
- Several Lyona luminaires will network together over 2,4GHz signal.

• Optional version with battery-powered emergency lighting available: automatic self-test

• Also available as a DALI version

• Housing made of impact-resistant polycarbonate IK10

• Weatherproof design: IP65 for outdoor installation under canopies or in bathrooms

Number of lights on a 16B circuit breaker: 32

Areas of application:

Stairwells, hotels/offices, sanitary facilities, hallways/rooms,

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de

Technical Details:

Luminous Flux	4000 lm
Light Yield:	125 lm/W
Light Temperature:	2700, 3000, 4000 K
Color Rendering Index (CRI)	≥80 Ra
Color Consistency (SDCM):	3
Power Consumption:	12, 17, 23, 32 W
Power Factor (PF):	0.9
Operating Hours:	>100.000 h L80/B50
Switching Cycles:	>100.000
Ignition Time:	<0,5 s
Ambient Temperature (TA):	-25°C - 40°C
Housing Material:	Polycarbonat
Housing Color	white
Dimensions	400x69 mm
Net Weight:	1450 g
Warranty	5 years

Information and Downloads:

