

BREVIA SWING MKII 8-927-957-720lm Triac Dim GST-18 Terminal Box



Product information "BREVIA SWING MKII 8-927-957-720lm Triac Dim GST-18 Terminal Box"

very flat recessed LED luminaire

- compact dimensions, robust housing made of aluminum just 24mm high
- selectable CCT color via switch: 2700/3000/4000/5700K BI-color COB with high CRI >90
- flickerfree light
- widely protected against dust and humidity (frontside IP44)
- dimmable via TRIAC: trailing- or leading edge dimming
- Suitable for 68-75mm cutouts
- Easy installation via included connection terminal with relief
- built-in LED driver
- tiltable light beam +/-10°
- available in 3 different housing colors: black, white, satin-nickel

Applications:

- Entrance hall, sanitary facilities, offices, living rooms, hotel, shop

Technical Details:

Luminous Flux	720 lm
Light Yield:	94 lm/W
Light Temperature:	2700, 3000, 4000, 5700 K
Color Rendering Index (CRI)	≥90 Ra
Color Consistency (SDCM):	4
Power Consumption:	8 W
Operating Hours:	>54.000 h L80/B50
Switching Cycles:	>50.000
Ignition Time:	<0,5 s
Ambient Temperature (TA):	-10°C - 35°C
Housing Material:	Aluminium/PC
Housing Color	black
Coating:	powder-coated
Pivot Range tilt:	60 °
Dimensions	90x25 mm
Cut-Out Dimensions	68-75 mm
Net Weight:	230 g
Warranty	5 years

Information and Downloads:

