

Vatura IP 14-827-840-1400lm IP65 IK10



Size: Ø300*H100mm
Ø400*H100mm

Technical Details:

Luminous Flux:	1400 lm
LED Output:	25.2 W
Light Yield:	120 lm/W
Light Temperature:	3000,4000,5000 K
Light Color:	CCT Select
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<6
Beam Angle:	100 °
Light Emission:	downward
LED-Chip:	SMD 2835
Number of LED:	126
Ignition Time:	<0,5 s
Power Consumption:	Power Select (9, 12, 14 W)
Contains Driver:	✓
Driver Manufacturer:	Foshan Rayven
Power Factor (PF):	>0.7
Input Driver:	terminal
Output of Driver:	DC 27-42V, 300mA
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	Terminal
Switching Cycles:	>50.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-10°C - 45°C
Storage Temperature:	-40°C - 60°C

Dimensions:	320x80 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	65
IK Code:	10
Housing Color	mattwhite
Housing Material:	PC/ABS
Coating:	lacquered
Special Feature of Housing:	wetterfest und schlagzäh
Cover:	opal
Net Weight:	891 g
Type of Packaging:	box
Dimensions of Packaging:	320x320x80
Weight incl. Packaging:	1.084 kg
Content Master Package:	10
Dimensions of Master Package:	670x450x345 mm
Weight Master Package:	11,7 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557827391
Ideal für Flur und Treppenhäuser	
Perfect for corridors and staircase house	
Kann im Freien unter Vordächer verwendet werden!	
Can be used temporarily outdoor under canopies	
Option: Sensor & Battery Emergency Module	

Information and Downloads:

