Technical Data Sheet

Order number: LG65046DA

LITEGEAR
LED Lighting Solutions

Lucello Multi-CCT BL-Panel 6262-36-830/840-5040LM BAP UGR<19 DALI Dim









Technical Details:

Luminous Flux:	5040 lm
LED Output:	36 W
Light Yield:	140 lm/W
Light Temperature:	3000,3500,4000 K
Light Color:	CCT Select
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<6
Beam Angle:	90 °
Unified Glare Rating (UGR):	<19
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	DALI,Push-Dim
LED-Chip Manufacturer:	JINRUI
LED-Chip:	SMD
Number of LED:	128
Ignition Time:	<0,5 s
Input Current:	AC 220-240V, 220mA, 50/60Hz
Power Consumption:	Power Select (24-30-36 W)
Contains Driver:	✓
Driver Manufacturer:	Lifud
Power Factor (PF):	>0.9
Input Driver:	terminal
Output of Driver:	DC 36V, 600-900mA
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	Terminal
Switching Cycles:	>50.000
Electrical Protection Class:	II

Dimensions:	620x620x35 mm
Cut-Out Dimensions:	610x610 mm
Mounting:	Decke
Montageart:	recessed
IP Class:	20 (20 room side)
IK Code:	02
Housing Color	white
Housing Color (RAL Code):	similar 9003
Housing Material:	Aluminium + plastic
Coating:	powder-coated
Cover:	prismatic
Net Weight:	2000 g
Type of Packaging:	box
Dimensions of Packaging:	643x675x41
Weight incl. Packaging:	2.25 kg
Content Master Package:	5
Dimensions of Master Package:	655x225x695 mm
Weight Master Package:	13,5 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	70.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557827926
Bildschirmarbeitsplatz tauglich nach EN 12464-1	
CCT-Select: schaltbare Lichtfarbe 3000,3500,4000K	
Backlite Technology, Dali 2 & Push Dim	
OneFitAll	

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de

Storage Temperature:	-20°C - 40°C

Information and Downloads: