

RETROVA SELECT 120 25/40-CCT-Select-3250-5300LM



Leistung: 38W
 0.9m Version: 25, 30, 35, 40W
 1.2m Version: 25, 30, 35, 40W
 2.4m Version: 25, 30, 35, 40W



Technical Details:

Luminous Flux:	5300 lm
LED Output:	38 W
Light Yield:	133 lm/W
Light Temperature:	3000,4000,5000 K
Light Color:	CCT Select
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<3
Beam Angle:	120 °
Unified Glare Rating (UGR):	<25
Light Emission:	downward
LED-Chip Manufacturer:	Osram Opto Semiconductors
LED-Chip:	SMD 2835
Number of LED:	456
Ignition Time:	<0,5 s
Input Current:	AC 198 - 264V, 50/60Hz, DC 176 - 276V
Power Consumption:	Power Select (25,30,35,40 W)
Contains Driver:	✓
Driver Manufacturer:	Osram
Power Factor (PF):	>0.95
Input Driver:	terminal
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	Terminal
Switching Cycles:	>100.000
Electrical Protection Class:	I
Compatible with Emergency Current:	✓
Ambient Temperature (TA):	-20°C - 45°C
Storage Temperature:	-20°C - 55°C

Dimensions:	1190x96x74 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	66
IK Code:	08
Housing Color	lichtgrey
Housing Material:	ABS
Special Feature of Housing:	schlagzäh
Cover:	prismatic
Net Weight:	1557 g
Dimensions of Packaging:	1220x100x82
Weight incl. Packaging:	1.736 kg
Content Master Package:	10
Dimensions of Master Package:	1240x430x220 mm
Weight Master Package:	1901 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405114090
Certifications	CE,D
Barcode:	4250557823867
Osram LED Treiber mit einstellbarem Ausgangsstrom:	
Leistung einstellbar: 25,30,35,40W max. 142lm/W	
EVG: ENEC-10/VDE/EMC/EL/CE; geeignet für Notstrom	
Anzahl pro Automat: 10A: 20, 16A: 32 Stück	
CCT Select: 3000K, 4000K, 5000K by switch	

