Product Information

Order number: LG32231

Modulux Linear LED- Modul WF-600-18/24-930-940-3624lm-WH-CCT









Technical Details:

Luminous Flux	3624 lm
Light Yield:	151 lm/W
Light Temperature:	3000, 3500, 4000 K
Color Rendering Index (CRI)	≥90 Ra
Color Consistency (SDCM):	6
Power Consumption:	18, 20, 22, 24 W
Power Factor (PF):	0.95
Operating Hours:	>100.000 h L80/B50
Switching Cycles:	>100.000
Ignition Time:	<1 s
Ambient Temperature (TA):	-25°C - 60°C
Housing Material:	aluminum
Housing Color	white
Coating:	powder-coated
Dimensions	600x61x66 mm
Net Weight:	650 g
Warranty	5 years

Information and Downloads:

Product information "Modulux Linear LED- Modul WF-600-18/24-930-940-3624lm-WH-CCT"

Linear LED tracklight for 3-phase trackrails

Elegant, flat LED luminaire with integrated 3-phase track adapter which is completely integrated in the standard track rails. Ultra flat appearance only 12mm high and 60mm wide. Available with symmetrical 60/90/120° or asymmetrical light dispersion 2 x 30° with multi-lens panel. Ideal for illuminating supermarket shelves, retail areas, exhibition halls, extremely high luminous flux up to 9200 lumens with only 24W consumption corresponding to up to 151 lumens / watt.

- Easy and fast installation using 3-phase trackrail adapters.
- 3 selectable power phases, compatible with all common track systems
- Adjustment output power: Adjustable LED driver 18, 20, 22, 24Watt
- CCT switchable: 3000K, 3500K, 4000K
- Modular structure of the diffusor or lens panel
- The individual modules can be seamlessly lined up. It creates the impression of a continuous line of light.
- Good heat dissipation and optimal light distribution
- Also available with dimmable Dali driver on request.
- Available in 2 housing colors: black, white optional also in silver (clarify minimum quantity beforehand)

5000K, 6000K
- available in two lengths: 60cm and 150cm