Product Information

**Order number: LG32236BK**

# Modulux Linear LED- Modul WF-150-35/50-930-940-7000lm-BK-CCT









## Technical Details:

| | |
|---|---|
| **Luminous Flux** | 6600 lm |
| **Light Yield:** | 131 lm/W |
| **Light Temperature:** | 3000, 3500, 4000 K |
| **Color Rendering Index (CRI)** | ≥90 Ra |
| **Color Consistency (SDCM):** | 3 |
| **Power Consumption:** | 35, 40, 45, 50 W |
| **Power Factor (PF):** | 0.95 |
| **Operating Hours:** | >100.000 h L80/B50 |
| **Switching Cycles:** | >100.000 |
| **Ignition Time:** | <1 s |
| **Ambient Temperature (TA):** | -25°C - 60°C |
| **Housing Material:** | aluminum |
| **Housing Color** | black |
| **Coating:** | powder-coated |
| **Dimensions** | 1493x61x66 mm |
| **Net Weight:** | 1108 g |
| **Warranty** | 5 years |

Information and Downloads:

## Product information "Modulux Linear LED-Modul WF-150-35/50-930-940-7000lm-BK-CCT"

Linear LED tracklight for 3-phase trackrails

Elegant, flat LED luminaire with integrated 3-phase track adapter which is completely integrated in the standard track rails. Ultra flat appearance only 12mm high and 60mm wide. Available with symmetrical 60/90/120° or asymmetrical light dispersion 2 x 30° with multi-lens panel. Ideal for illuminating supermarket shelves, retail areas, exhibition halls, extremely high luminous flux up to 9200 lumens with only 50W consumption corresponding to up to 131 lumens / watt.

- Easy and fast installation using 3-phase trackrail adapters.
- 3 selectable power phases, compatible with all common track systems
- Adjustment output power: Adjustable LED driver 35, 40, 45, 50Watt
- CCT switchable: 3000K, 3500K, 4000K
- Modular structure of the diffusor or lens panel
- The individual modules can be seamlessly lined up. It creates the impression of a continuous line of light.
- Good heat dissipation and optimal light distribution
- Also available with dimmable Dali driver on request.
- Available in 2 housing colors: black, white optional also in silver (clarify minimum quantity beforehand)

5000K, 6000K
- available in two lengths: 60cm and 150cm