

# Modulux Linear LED- Modul 150-35/50-930-940-7100lm-BK-CCT



## Product information "Modulux Linear LED- Modul 150-35/50-930-940-7100lm-BK-CCT"

Linear LED tracklight for 3-phase trackrails

Elegant, flat LED luminaire with integrated 3-phase track adapter which is completely integrated in the standard track rails. Elegant, ultra flat appearance only 11mm high and 60mm wide. Available with symmetrical 60/90/120° or asymmetrical light dispersion 2 x 45° with multi-lens panel. Ideal for illuminating supermarket shelves, retail areas, exhibition halls, extremely high luminous flux up to 9200 lumens with only 50W consumption corresponding to up to 142 lumens / watt.

- Easy and fast installation using 3-phase trackrail adapters.
- 3 selectable power phases, compatible with all common track systems
- Adjustment output power: Adjustable LED driver 35, 40, 45, 50Watt
- selectable light colour: CCT select: 3000K, 3500K, 4000K
- Modular structure of the lens panel
- The individual modules can be seamlessly lined up. It creates the impression of a continuous line of light.
- Good heat dissipation and optimal light distribution
- Also available with dimmable Dali driver on request.
- Available in 2 housing colors: black, white optional also in silver (clarify minimum quantity beforehand)



### Technical Details:

|                             |                    |
|-----------------------------|--------------------|
| Luminous Flux               | 7100 lm            |
| Light Yield:                | 142 lm/W           |
| Light Temperature:          | 3000, 3500, 4000 K |
| Color Rendering Index (CRI) | ≥90 Ra             |
| Color Consistency (SDCM):   | 4                  |
| Power Consumption:          | 35, 40, 45, 50 W   |
| Power Factor (PF):          | 0.95               |
| Operating Hours:            | >100.000 h L80/B50 |
| Switching Cycles:           | >100.000           |
| Ignition Time:              | <1 s               |
| Ambient Temperature (TA):   | -25°C - 60°C       |
| Housing Material:           | aluminum           |
| Housing Color               | black              |
| Coating:                    | powder-coated      |
| Dimensions                  | 1493x61x30 mm      |
| Net Weight:                 | 1300 g             |
| Warranty                    | 5 years            |

Information and Downloads:



5000K, 6000K

- available in two lengths: 60cm and 150cm