Technical Data Sheet

Order number: LG32284DABK

LITEGEAR
LED Lighting Solutions

MODULUX OFFICE Linear LED- Modul 60-18/24-940-3510lm-BK DALI DIM







Technical Details:

Luminous Flux:	3510 lm
LED Output:	24 W
Light Yield:	140 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥90 Ra
Color Consistency (SDCM):	<3
Beam Angle:	60 °
Unified Glare Rating (UGR):	<19
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	DALI,Push-Dim
LED-Chip Manufacturer:	Ebright
LED-Chip:	SMD 2835
Number of LED:	96
Ignition Time:	<1 s
Input Current:	AC 220-240V, 330mA, 50/60Hz
Power Consumption:	Power Select (18,20,22,24 W)
Contains Driver:	✓
Driver Manufacturer:	Coreshine
Power Factor (PF):	>0.95
Input Driver:	lighting track
Output of Driver:	DC 85-144V
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	Power rail
Switching Cycles:	>100.000
Electrical Protection Class:	I
Ambient Temperature (TA):	-20°C - 60°C

Dimensions:	600x62x20 mm
Mounting:	Decke,Stromschiene
Montageart:	surface mounted
IP Class:	40
IK Code:	04
Housing Color	black
Housing Color (RAL Code):	similar 9017
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	3-Phase adapter
Cover:	Louver
Net Weight:	800 g
Type of Packaging:	none
Dimensions of Packaging:	680x350x240
Weight incl. Packaging:	1 kg
Content Master Package:	10
Dimensions of Master Package:	680x350x240 mm
Weight Master Package:	10 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	100.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE,TÜV
Barcode:	4250557828459
Spezial Optik für Büro, Showroom, Kassenzone	
Special optics for office, showroom, cashier area	
60° symmetric	
Power adjust: 18/20/22/24W	
Für 3-Phasenstromschien/ for 3 phase trackrail	

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de

Information and Downloads: