

Astrum Line MKIII Röhre 1500 25-860-4000LM



Technical Details:

Luminous Flux:	4000 lm
LED Output:	25 W
Light Yield:	160 lm/W
Light Temperature:	6000 K
Light Color:	daylight
Color Rendering Index:	≥82 Ra
Color Consistency (SDCM):	<3
Beam Angle:	140 °
Light Emission:	downward
LED-Chip:	SMD 2835
Number of LED:	192
Ignition Time:	<1 s
Input Current:	AC 100 - 240V, 50/60Hz
Power Consumption:	25 W
Contains Driver:	✓
Power Factor (PF):	>0.95
Output of Driver:	DC 70 - 75V
CC/CV:	CC
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 45°C

Dimensions:	26x1512 mm
Length of Tube:	1500 mm
Socket:	G13
Rotating Socket:	✓
IP Class:	40
Housing Color	white
Housing Material:	plastic
Special Feature of Housing:	Aluprofil inside
Cover:	frosted
Net Weight:	366 g
Type of Packaging:	box
Dimensions of Packaging:	35x35x1590
Weight incl. Packaging:	0.449 kg
Content Master Package:	25
Dimensions of Master Package:	1620x250x250 mm
Weight Master Package:	17,47 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L70/B20
Disposal Obligation:	✓
Customs Tariff Number:	950540999
Certifications	CE,TÜV,LM79,LM80
Barcode:	4250557822105
drehbare Endkappe	
turnable endcap	

Information and Downloads:

