


Order number: LG58917WHUPCCT

NOVALOOP Ring Light 150060-80-930/960-8000lm Up/Down Dali Dim



Technical Details:

Luminous Flux:	8000 lm
Light Yield:	110 lm/W
Light Temperature:	3000-6000 K
Light Color:	CCT Select
Color Rendering Index:	≥95 Ra
Color Consistency (SDCM):	<3
Beam Angle:	90 °
Unified Glare Rating (UGR):	<22
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	DALI, Push-Dim
LED-Chip Manufacturer:	Everlight
LED-Chip:	SMD 2835
Number of LED:	702
Ignition Time:	<0,5 s
Input Current:	AC 220 - 240V, 393,1mA, 50/60Hz
Power Consumption:	80 W
Contains Driver:	✓
Driver Manufacturer:	Sunricher
Power Factor (PF):	>0.96
Input Driver:	lighting track
Output of Driver:	DC 6-42V, 2000mA
CC/CV:	CC
Input Lamp:	Terminal
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-25°C - 45°C

Dimensions:	1500x60 mm
Mounting:	Deckenabhängung
Montageart:	surface mounted
IP Class:	20 (20 room side)
Housing Color	white
Housing Color (RAL Code):	similar 9003
Housing Material:	aluminum
Coating:	powder-coated
Cover:	opal
Net Weight:	10900 g
Type of Packaging:	box
Dimensions of Packaging:	1550x1550x110
Weight incl. Packaging:	17.9 kg
Content Master Package:	1
Weight Master Package:	17,9 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	79.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE, LM80, SELV
Barcode:	4250557827766
200cm Seilabhängung + Deckenanschlußdose	
DALI DT8 Dimmung dual white	

Information and Downloads:

