


NOVALOOP Ring Light 120060-60-830-6600lm Dali



Technical Details:

Luminous Flux:	6600 lm
Light Yield:	120 lm/W
Light Temperature:	3000 K
Light Color:	warmwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<3
Beam Angle:	120 °
Unified Glare Rating (UGR):	<21
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	DALI
LED-Chip:	SMD2835
Number of LED:	936
Ignition Time:	<0,5 s
Input Current:	AC 220 - 240V, 0,36mA, 50/60Hz
Power Consumption:	55 W
Contains Driver:	✓
Driver Manufacturer:	Boke
Power Factor (PF):	>0.95
Input Driver:	lighting track
Output of Driver:	DC 6-42V, 1500mA
CC/CV:	CV
Output Current Adjustable:	✓
Input Lamp:	Terminal
Switching Cycles:	>50.000
Electrical Protection Class:	II
Compatible with Emergency Current:	✓

Dimensions:	1200x60 mm
Cut-Out Dimensions:	35 mm
Mounting:	Deckenabhängung
Montageart:	surface mounted
IP Class:	20
IK Code:	10
Housing Color	black matt
Housing Color (RAL Code):	similar 9003
Housing Material:	aluminum
Coating:	powder-coated
Cover:	clear
Net Weight:	5670 g
Type of Packaging:	box
Dimensions of Packaging:	1250x1250x100
Content Master Package:	1
Dimensions of Master Package:	1250x1250x100 mm
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	100.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE,ENEC
Barcode:	4250557827285
inkl. 200cm Seilabhängung + Deckenanschlußdose	
Dali Dimmung	

Information and Downloads:

