Product Information

Order number: LG10480

OMNIA Downlight 4/6-60-927/960-600LM max. IP65 front Triac Dim









Product information "OMNIA Downlight 4/6-60-927/960-600LM max. IP65 front Triac Dim"

Litegear ® universal LED-Downlight - One Fit all

- Triac dimmable Downlight for leading- or trailing edge dimming
- perfect replacement for konventional downlights with halogen MR16 GU5,3 or GU10 socket
- Damp proof luminaire IP65 front
- interchangeable magnetic bezel (white color ring included)
- high system effcency up to 105lm/W (440-660lm) High CRI: >90
- Power select: 4/6W switchable
- CCT selectable 2700, 3000, 4000, 6000 Kelvin via switch behind the bezel
- optional other bezel colours available: black, silver brushed
- beamangle: 60°
- compact dimensions: 88mm Dimensions: and only 35mm high for recessed ceilings with limited space cut out: 68-70mm only 32mm deep
- plugable terminal box for power loop 240V AC
- Master/Slave function: 1 to 2 Omnia Smart Downlights can control several pasive Omnia downlight from same range up to 200W load as salves

Applications:
hall way, storage rooms, toilet, dressing room, seller, balcony, entrance door, outside under cannopies, Terrace,attica, walkways

Technical Details:

Luminous Flux	600 lm
Light Yield:	110 lm/W
Light Temperature:	2700, 3000, 4000, 6000 K
Color Rendering Index (CRI)	≥90 Ra
Color Consistency (SDCM):	6
Power Consumption:	4, 6 W
Power Factor (PF):	0.5
Operating Hours:	>50.000 h L70/B50
Switching Cycles:	>100.000
Ignition Time:	<0,5 s
Ambient Temperature (TA):	-20°C - 40°C
Housing Material:	Aluminium/PC
Housing Color	black/white
Coating:	powder-coated
Dimensions	88x40 mm
Cut-Out Dimensions	68-70 mm
Net Weight:	144 g
Warranty	3 years

Information and Downloads:

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de