


NOVALOOP Ring Light 60060-36-930/960-3600lm Up/Down Dali DT8 Dim



Technical Details:

Luminous Flux:	3600 lm
Light Yield:	100 lm/W
Light Temperature:	3000-6000 K
Light Color:	CCT Select
Color Rendering Index:	≥92 Ra
Color Consistency (SDCM):	<3
Beam Angle:	110 °
Unified Glare Rating (UGR):	<22
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	DALI, Push-Dim, DALI-2
LED-Chip Manufacturer:	Everlight
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Input Current:	AC 220 - 240V, 50/60Hz
Power Consumption:	36 W
Contains Driver:	✓
Power Factor (PF):	>0.95
Input Driver:	terminal
Output of Driver:	DC 6-42V, 900mA
CC/CV:	CC
Input Lamp:	Terminal
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-25°C - 45°C
Storage Temperature:	-40°C - 80°C

Dimensions:	600x60 mm
Mounting:	Deckenabhängung
Montageart:	surface mounted
IP Class:	20 (20 room side)
Housing Color	white
Housing Color (RAL Code):	similar 9003
Housing Material:	aluminum
Coating:	powder-coated
Cover:	prismatic
Net Weight:	5500 g
Type of Packaging:	box
Dimensions of Packaging:	650x650x110
Content Master Package:	1
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	79.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE, LM80, SELV
200cm Seilabhängung + Deckenanschlußdose	
DALI Dimmung DT8 Dual White CCT adjust	
schaltbares Up Light	

Information and Downloads:

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de

