

Order number: LG58916BKUPCCT

NOVALOOP Ring Light 120060-60-930/960-6000lm Up/Down Dali DT8 Dim



Product information "NOVALOOP Ring Light 120060-60-930/960-6000lm Up/Down Dali DT8 Dim"

Pendant ring luminaire with DALI-2 dimming
 High CRI >92 Ra; CCT adjustment (3000-6000 K) via DALI DT8

Novaloop is a timeless luminaire series featuring a beautifully crafted aluminum housing available in black or white. Includes cable suspension and a dimmable LED driver.

Provides both direct and indirect light distribution.


Curved, powder-coated extruded aluminum profile (60 mm high, 60 mm wide).

Connection via ceiling canopy with 2 m steel cable.

- Superior color rendering
- Elegant, timeless design
- Switchable indirect light
- Stepless dimming and color adjustment via DALI DT8
- Optionally controllable via app adapter (e.g., Meshle, Casambi)
- Available in black, white, or custom colors

Applications:

Residential, retail spaces, hotels, hospitality, offices, decorative lighting, supermarkets, galleries, dental practices, medical practices



Technical Details:

Luminous Flux	6000 lm
Light Yield:	100 lm/W
Light Temperature:	3000-6000 K
Color Rendering Index (CRI)	≥92 Ra
Color Consistency (SDCM):	3
Power Consumption:	60 W
Power Factor (PF):	0.97
Operating Hours:	>79.000 h L80/B20
Switching Cycles:	>100.000
Ignition Time:	<0,5 s
Ambient Temperature (TA):	-25°C - 45°C
Housing Material:	aluminum
Housing Color	black
Coating:	powder-coated
Dimensions	1200x60 mm
Net Weight:	7800 g
Warranty	5 years

Information and Downloads:

