



Placida Clou 307-24-830-850-2600LM PIR SENSOR OneFitAll IP54



Technical Details:

Luminous Flux:	2640 lm
LED Output:	24 W
Light Yield:	110 lm/W
Light Temperature:	3000/4000/5000 K
Light Color:	CCT Select
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	115 °
Unified Glare Rating (UGR):	<23
Light Emission:	downward
LED-Chip Manufacturer:	Lextar
LED-Chip:	SMD 2835
Number of LED:	192
Ignition Time:	<0,5 s
Input Current:	AC 220-240V, 109mA, 50/60Hz
Power Consumption:	Power Select (12, 18, 24 W)
Contains Driver:	✓
Power Factor (PF):	>0.8
Input Driver:	terminal
Output of Driver:	DC 87V, 233mA
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	Terminal
Switching Cycles:	>30.000
Electrical Protection Class:	II
Loop-Through Cabling:	✓
Ambient Temperature (TA):	-20°C - 45°C
Storage Temperature:	-20°C - 45°C

Dimensions:	307x24 mm
Installation Depth:	22 mm
Cut-Out Dimensions:	90-280 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	54 (54 room side)
IK Code:	03
Housing Color	white
Housing Color (RAL Code):	similar 9016
Housing Material:	plastic
Special Feature of Housing:	Farbwahlschalter 830-850
Cover:	opal
Net Weight:	739 g
Type of Packaging:	box
Dimensions of Packaging:	315x315x31
Weight incl. Packaging:	0.89 kg
Content Master Package:	10
Dimensions of Master Package:	335x335x340 mm
Weight Master Package:	9,88 kg
Product Line:	Essential Line
Warranty	3 years
Operating Hours:	30.000 h L70/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405114090
Certifications	CE
Barcode:	4250557827957
Über Schalter wählb. Lichtfarbe 3000, 4000, 5000K	
Eingebauter IR-Bewegungsmelder/ PIR Sensor	



Durchgangsverdrahtung, Orientierungslicht

Vielseitige Einsatzmöglichkeiten, Power Select