


DURATA Advance X Connector ca. 4W



Technical Details:

Luminous Flux:	480 lm
Light Yield:	120 lm/W
Light Temperature:	3000, 3500, 4000 K
Light Color:	CCT Select
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<3
Beam Angle:	2x90 °
Unified Glare Rating (UGR):	<19
Light Emission:	
Dimmable:	✓
Method of Dimming:	DALI, Push-Dim
LED-Chip Manufacturer:	San'an
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Power Consumption:	4 W
Contains Driver:	✓
Power Factor (PF):	>0.9
Input Driver:	plug connector
Output of Driver:	DC 24-42V
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-10°C - 40°C
Storage Temperature:	-20°C - 55°C

Dimensions:	267x50x100 mm
Mounting:	Decke
Montageart:	surface mounted
IP Class:	20 (20 room side)
IK Code:	05
Housing Color	mattwhite
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	Interconnectable
Cover:	prismatic
Type of Packaging:	box
Product Line:	Premio Line
Warranty	5 years
Operating Hours:	50.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405429000
Certifications	CE
Elegante, modulare Lichtlinienleuchte für Büros	
Dali 2 Dim CCT Select 3000, 3500, 4000K	
Einspeisung über DC vom Treiber der Leuchte	
70% downlight, 30% up light	

Information and Downloads:

