

DURATA Advance 30-830/840-3600LM UP/DOWN UGR DALI 2 DIM



Technical Details:

Luminous Flux:	3600 lm
Light Yield:	120 lm/W
Light Temperature:	3000, 3500, 4000 K
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<3
Beam Angle:	2x90 °
Unified Glare Rating (UGR):	<19
Light Emission:	
Dimmable:	✓
Method of Dimming:	DALI,Push-Dim,DALI-2
LED-Chip Manufacturer:	San'an
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Input Current:	AC 200-240V, 200mA, 50/60Hz
Power Consumption:	30 W
Contains Driver:	✓
Driver Manufacturer:	Boke
Power Factor (PF):	>0.95
Input Driver:	plug connector
Output of Driver:	DC 24-42V, 750mA
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	plug connector
Switching Cycles:	>100.000
Electrical Protection Class:	I
Ambient Temperature (TA):	-10°C - 40°C
Storage Temperature:	-20°C - 55°C

Dimensions:	1200x50x100 mm
Mounting:	Decke
Montageart:	surface mounted
IP Class:	20 (20 room side)
IK Code:	05
Housing Color	black matt
Housing Color (RAL Code):	similar 9005
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	Interconnectable
Cover:	prismatic
Net Weight:	3420 g
Type of Packaging:	box
Content Master Package:	6
Dimensions of Master Package:	1235x200x265 mm
Product Line:	Premio Line
Warranty	5 years
Operating Hours:	60.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405429000
Certifications	CE
Elegante, modulare Lichtlinienleuchte für Büros	
Dali 2 Dim CCT Select 3000, 3500, 4000K	
Zuleitung und 250cm Stahlseil enthalten enthalten	
2700lm direkt, 900lmindirekt	

Information and Downloads:

