Product Information

Order number: LG60008E

Emergy Brick PRO 1,5-740-250lm SC WH







Technical Details:

Luminous Flux	250 lm
Light Yield:	166 lm/W
Light Temperature:	4000 K
Color Rendering Index (CRI)	≥70 Ra
Color Consistency (SDCM):	6
Power Consumption:	2 W
Power Factor (PF):	0.5
Operating Hours:	>50.000 h L70/B30
Switching Cycles:	>25.000
Ignition Time:	<1 s
Ambient Temperature (TA):	0°C - 40°C
Housing Material:	Polycarbonat
Housing Color	white
Dimensions	351x109x50 mm
Net Weight:	470 g
Warranty	5 years

Information and Downloads:

Product information "Emergy Brick PRO 1,5-740-250lm SC WH"

LED escape route light with self test fuction

Emergency light with single battery supply for escape route lighting. 3 hours emergency lighting with Li-Ion battery 2500mAh, 3.6V. Can also be used as escape route pictogram light. Pictogram with cutable directional arrow is enclosed. Good brightness and wide dispersion. LED light source with long life up to 50,000 hours. LED status display via green status LED. Nice, rectangular water- and dustproof IP65 body made of plastic. Permanent phase monitoring. Emergency battery operation: 3 hours.
Inkl. exit direction signs: arrow left, right, down
Manufactured to comply EN62034: 2012,EN 60598-2-22

- Operating device: emergency / mains: electronic ballast
- Beam angle: symmetrical> 120 °
- LED: 1,5W
- Luminous flux: typ. 250 lumens
- Incl. pictogram with cutable directional arrow and person symbol
- Dimensions: see drawing
- viewing distance 20m

This is a self-test luminaire. Functional test is carried out automatically once a week and runs
for 30 seconds. Full duration test is carried out automatically every 52 weeks. First full duration
test is carried out automatically within the first 4 weeks after the luminaire being connected to
mains voltage. This luminaire can be used in conjunction with the Advanced Remote Control
(ARC). ARC is an optional tool that adds extra features to AST emergency luminaires. Please
refer to the ARC's user guide

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de