


Integra SMD MKII 26-840-3510LM



Technical Details:

Luminous Flux:	3510 lm
LED Output:	25 W
Light Yield:	135 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<5
Beam Angle:	83 °
Unified Glare Rating (UGR):	<19
Light Emission:	downward
LED-Chip Manufacturer:	San'an
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Power Consumption:	26 W
Output of Driver:	DC 30 - 36V, 700mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>100.000
Ambient Temperature (TA):	-20°C - 40°C

Dimensions:	217x121 mm
Installation Depth:	121 mm
Cut-Out Dimensions:	204 mm
Mounting:	Decke
Montageart:	recessed
IP Class:	54 (65 room side)
IK Code:	08
Housing Color	white
Housing Material:	aluminum
Coating:	lacquered
Cover:	clear
Net Weight:	1060 g
Type of Packaging:	box
Dimensions of Packaging:	240x240x140
Weight incl. Packaging:	1.255 kg
Content Master Package:	10
Dimensions of Master Package:	720x260x500 mm
Weight Master Package:	13,45 kg
Product Line:	Essential Line
Warranty	5 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405409990
Certifications	CE,LM80
Barcode:	4250557810645
ohne Vorschaltgerät! bei Zubehör pass. EVG wählen	
without power supply! choose driver in accessories	
IP54 raumseitig/from room side	

Information and Downloads:

