

Integra RS Recessed Spotlight



Technical Details:

Luminous Flux:	2850 lm
LED Output:	36 W
Light Yield:	75 lm/W
Light Temperature:	3000 K
Light Color:	warmwhite
Color Rendering Index:	≥80 Ra
Beam Angle:	36 °
Swappable Reflector:	✓
Light Emission:	upward
LED-Chip Manufacturer:	Sharp
LED-Chip:	COB
Number of LED:	1
Ignition Time:	<1 s
Input Current:	AC 100 - 240V, 50/60Hz
Power Consumption:	38 W
Contains Driver:	✓
Power Factor (PF):	>0.94
Input Driver:	terminal
Output of Driver:	DC 50V, 1050mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>25.000
Ambient Temperature (TA):	-20°C - 40°C

Dimensions:	190x172 mm
Cut-Out Dimensions:	165 mm
Mounting:	Decke
Pivot Range pan:	350 °
Pivot Range tilt:	50 °
IP Class:	20
Housing Color	white
Housing Color (RAL Code):	similar 9016
Housing Material:	aluminum
Coating:	lacquered
Net Weight:	1082 g
Type of Packaging:	box
Weight incl. Packaging:	1.589 kg
Warranty	3 years
Operating Hours:	35.000 h L70/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557803722

Information and Downloads:



