


Paraflecta? Downlight 5-828-380LM



Technical Details:

Luminous Flux:	380 lm
LED Output:	5 W
Light Yield:	76 lm/W
Light Temperature:	2800 K
Light Color:	warmwhite
Color Consistency (SDCM):	<6
Beam Angle:	38 °
Light Emission:	downward
Dimmable:	✓
LED-Chip Manufacturer:	Sharp
LED-Chip:	COB
Number of LED:	1
Ignition Time:	<1 s
Input Current:	AC 220 - 240V, 50/60Hz
Power Consumption:	5 W
Contains Driver:	✓
Power Factor (PF):	>0.8
Input Driver:	cable with flying leads
Output of Driver:	DC 18 - 32V, 255mA
CC/CV:	CC
Input Lamp:	plug connector
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 40°C

Dimensions:	85x71 mm
Installation Depth:	71 mm
Cut-Out Dimensions:	72 mm
Mounting:	Decke
Montageart:	recessed
Pivot Range tilt:	25 °
Housing Color	silver
Housing Material:	aluminum
Net Weight:	350 g
Type of Packaging:	box
Weight incl. Packaging:	0.303 kg
Product Line:	Advance Line
Warranty	2 years
Operating Hours:	30.000 h L70/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557805498

Information and Downloads:



