

Copula 10-830-680LM



Technical Details:

Luminous Flux:	680 lm
LED Output:	9 W
Light Yield:	68 lm/W
Light Temperature:	3000 K
Light Color:	warmwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<6
Beam Angle:	26 °
Unified Glare Rating (UGR):	<19
Light Emission:	downward
LED-Chip Manufacturer:	Epistar
LED-Chip:	COB
Number of LED:	1
Ignition Time:	<1 s
Input Current:	AC 220 - 240V, 50/60Hz
Power Consumption:	10 W
Contains Driver:	✓
Power Factor (PF):	>0.9
Input Driver:	terminal
Output of Driver:	DC 34V, 300mA
CC/CV:	CC
Input Lamp:	cable with flying leads
Switching Cycles:	>50.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 40°C

Dimensions:	79,5x1100 mm
Mounting:	Decke
Montageart:	surface mounted
IP Class:	20
Housing Color	white
Housing Material:	aluminum
Coating:	lacquered
Special Feature of Housing:	black heatsink
Cover:	clear
Net Weight:	774 g
Type of Packaging:	box
Dimensions of Packaging:	235x105x100
Weight incl. Packaging:	0.865 kg
Content Master Package:	30
Dimensions of Master Package:	670x280x320 mm
Weight Master Package:	25,0 kg
Product Line:	Essential Line
Warranty	3 years
Operating Hours:	30.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557808376

Information and Downloads:



