


ILLUNA Square 30-830-2400lm



Technical Details:

Luminous Flux:	2400 lm
LED Output:	30 W
Light Yield:	80 lm/W
Light Temperature:	3000 K
Light Color:	warmwhite
Color Rendering Index:	≥80 Ra
Beam Angle:	36 °
Light Emission:	downward
LED-Chip Manufacturer:	Sharp
LED-Chip:	COB
Number of LED:	1
Ignition Time:	<1 s
Input Current:	AC 220 - 240V, 50/60Hz
Power Consumption:	30 W
Contains Driver:	✓
Driver Manufacturer:	Tridonic
Power Factor (PF):	>0.95
CC/CV:	CC
Switching Cycles:	>30.000
Ambient Temperature (TA):	-20°C - 40°C

Dimensions:	150x150x120 mm
Installation Depth:	120 mm
Cut-Out Dimensions:	140x140 mm
Mounting:	Decke
IP Class:	20
Housing Color	black
Housing Material:	aluminum
Coating:	lacquered
Net Weight:	867 g
Type of Packaging:	box
Weight incl. Packaging:	0.944 kg
Product Line:	Essential Line
Warranty	2 years
Operating Hours:	30.000 h L70/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557808420

Information and Downloads:

