

Fenestra Rectangle Advanced



Technical Details:

Luminous Flux:	4800 lm
LED Output:	48 W
Light Yield:	100 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	110 °
Unified Glare Rating (UGR):	<21
Light Emission:	downward
LED-Chip:	SMD 5630
Ignition Time:	<0,5 s
Input Current:	AC 220-240V, 50/60Hz
Power Consumption:	48 W
Contains Driver:	✓
Driver Manufacturer:	Boke
Input Driver:	cable with flying leads
Output of Driver:	DC 30 - 42V, 1200mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>50.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 40°C
Storage Temperature:	-20°C - 55°C

Dimensions:	1495x295x12 mm
Mounting:	Decke
IP Class:	20
Housing Color	greywhite
Housing Material:	aluminum
Coating:	lacquered
Cover:	opal
Net Weight:	3913 g
Type of Packaging:	box
Weight incl. Packaging:	5.4 kg
Content Master Package:	4
Dimensions of Master Package:	1532x180x395 mm
Weight Master Package:	20, kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	50.000 h L70/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557807423

Information and Downloads:



