

Instatube OD 1200 20-840-1700LM



Technical Details:

Luminous Flux:	1700 lm
LED Output:	20 W
Light Yield:	85 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Beam Angle:	160 °
LED-Chip Manufacturer:	Epistar
LED-Chip:	SMD 2835
Ignition Time:	<1 s
Input Current:	AC 100 - 240V, 50/60Hz
Power Consumption:	20 W
Contains Driver:	✓
Power Factor (PF):	>0.96
Input Lamp:	cable with plug
Switching Cycles:	>20.000
Ambient Temperature (TA):	-20°C - 40°C

Dimensions:	28x1200 mm
Mounting:	ceiling,wall
IP Class:	65
Housing Color	white
Housing Material:	plastic
Cover:	opal
Net Weight:	599 g
Type of Packaging:	box
Weight incl. Packaging:	0.983 kg
Content Master Package:	12
Dimensions of Master Package:	1360x280x230 mm
Weight Master Package:	13,4 kg
Warranty	2 years
Operating Hours:	30.000 h L70/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557803128

Information and Downloads:

