


Astrum Line II LED-Röhre 900 14-840-1950LM



Technical Details:

Luminous Flux:	1950 lm
LED Output:	13 W
Light Yield:	139 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	180 °
Light Emission:	downward
LED-Chip:	SMD 2835
Ignition Time:	<1 s
Input Current:	AC 220 - 240V, 50/60Hz
Power Consumption:	14 W
Contains Driver:	✓
Power Factor (PF):	>0.9
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 45°C
Storage Temperature:	-20°C - 50°C

Dimensions:	26x898 mm
Length of Tube:	900 mm
Socket:	G13
Rotating Socket:	✓
IP Class:	40
Housing Color	white
Housing Material:	plastic
Special Feature of Housing:	Aluprofil inside
Cover:	opal
Net Weight:	360 g
Type of Packaging:	box
Content Master Package:	36
Dimensions of Master Package:	1302x244x225 mm
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	50.000 h L70/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,LM80
Barcode:	4250557819709
für VVG, KVG mit magnetisch.Vorschaltgerät/Starter	
for magnetic ballast only with starter	

Information and Downloads:

