

Fenestra Circle MKII 144 8-840-536LM



Technical Details:

Luminous Flux:	536 lm
LED Output:	8 W
Light Yield:	67 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Beam Angle:	120 °
Light Emission:	downward
LED-Chip:	SMD 2835
Ignition Time:	<1 s
Input Current:	AC 220 - 240V, 50/60Hz
Power Consumption:	8 W
Contains Driver:	✓
Power Factor (PF):	>0.95
Input Driver:	cable with flying leads
Output of Driver:	DC 25-42V, 180mA
CC/CV:	CC
Input Lamp:	plug connector
Ambient Temperature (TA):	-20°C - 50°C

Dimensions:	144x18 mm
Installation Depth:	18 mm
Cut-Out Dimensions:	125 mm
Mounting:	Decke
Montageart:	recessed
IP Class:	43
Housing Color	white
Housing Material:	aluminum
Coating:	lacquered
Cover:	opal
Net Weight:	276 g
Type of Packaging:	box
Dimensions of Packaging:	275x452x30
Weight incl. Packaging:	0.446 kg
Content Master Package:	20
Dimensions of Master Package:	470x485x300 mm
Weight Master Package:	9,27 kg
Warranty	3 years
Operating Hours:	35.000 h L70/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557809878

Information and Downloads:

