

Integra Line 1500-50-840-5000lm ohne Treiber



Technical Details:

Luminous Flux:	5000 lm
LED Output:	46 W
Light Yield:	106 lm/W
Light Temperature:	3800 K
Light Color:	neutralwhite
Color Rendering Index:	≥84 Ra
Color Consistency (SDCM):	<5
Beam Angle:	110 °
Light Emission:	downward
LED-Chip:	SMD 2835
Number of LED:	432
Ignition Time:	<0,5 s
Power Consumption:	47 W
Power Factor (PF):	>0.977
Input Driver:	terminal
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 40°C

Installation Depth:	70 mm
Cut-Out Dimensions:	1510x110 mm
Mounting:	ceiling,wall
Montageart:	recessed
IP Class:	40
IK Code:	04
Housing Color	white
Housing Material:	aluminum
Coating:	lacquered
Cover:	opal
Net Weight:	3410 g
Type of Packaging:	box
Dimensions of Packaging:	1553x158x85
Weight incl. Packaging:	4.3 kg
Content Master Package:	5
Dimensions of Master Package:	1573x178x450 mm
Weight Master Package:	24,5 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	50.000 h L70/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
PC cover	

Information and Downloads:

