

Fenestra Circle Eco 105 4-830-320LM



Product information "Fenestra Circle Eco 105 4-830-320LM"

LED Integration Panel

Litegear® Fenestra Circle LED recessed panel for installation in ceilings or plasterboard walls. Easy mounting by snap-in pin holder. Very homogeneous light distribution and exceptionally high brightness. Ideal for lighting of retail areas, lobbies, hallways or offices. Glare-free light thus also suitable for workstations. Within our Fenestra LED panels we use only high quality LED chips from renowned manufacturers. Fenestra LED panels can be ordered in different sizes and shapes: round or square. The cooling of the LEDs are embedded laterally over an aluminum frame. Litegear® panels be equipped with a good color rendering of CRI: 80 Ra or better. Thus, the color of the illuminated products can be reproduced with high fidelity.



Technical Details:

Luminous Flux	320 lm
Light Yield:	80 lm/W
Light Temperature:	3000 K
Color Rendering Index (CRI)	≥80 Ra
Power Consumption:	4 W
Power Factor (PF):	0.9
Operating Hours:	>35.000 h L70/B50
Switching Cycles:	>15.000
Ignition Time:	<1 s
Ambient Temperature (TA):	-20°C - 50°C
Housing Material:	aluminum
Housing Color	white
Coating:	lacquered
Dimensions	105x20 mm
Cut-Out Dimensions	95 mm
Net Weight:	150 g
Warranty	3 years

Information and Downloads:

