

Fenestra Circle Eco 105 4-830-320LM



Technical Details:

Luminous Flux:	320 lm
LED Output:	4 W
Light Yield:	80 lm/W
Light Temperature:	3000 K
Light Color:	warmwhite
Color Rendering Index:	≥80 Ra
Beam Angle:	120 °
Unified Glare Rating (UGR):	<22
Light Emission:	downward
Ignition Time:	<1 s
Input Current:	AC 85-265V, 50/60Hz
Power Consumption:	4 W
Contains Driver:	✓
Power Factor (PF):	>0.9
Input Driver:	cable with flying leads
Output of Driver:	DC 18 - 22V
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>15.000
Ambient Temperature (TA):	-20°C - 50°C

Dimensions:	105x20 mm
Installation Depth:	18 mm
Cut-Out Dimensions:	95 mm
Mounting:	Decke
IP Class:	20
Housing Color	white
Housing Material:	aluminum
Coating:	lacquered
Cover:	opal
Net Weight:	150 g
Type of Packaging:	box
Warranty	3 years
Operating Hours:	35.000 h L70/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557812151

Information and Downloads:

