

Fenestra Circle Eco 200 15-840-1200LM



Technical Details:

Luminous Flux:	1200 lm
LED Output:	15 W
Light Yield:	80 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Beam Angle:	120 °
Unified Glare Rating (UGR):	<22
Light Emission:	downward
Ignition Time:	<1 s
Input Current:	AC 220-240V, 50/60Hz
Power Consumption:	15 W
Contains Driver:	✓
Power Factor (PF):	>0.9
Input Driver:	cable with flying leads
Output of Driver:	DC 30-42V, 350mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>35.000
Ambient Temperature (TA):	-20°C - 50°C

Dimensions:	200x20 mm
Installation Depth:	18 mm
Cut-Out Dimensions:	185 mm
Mounting:	Decke
IP Class:	20
Housing Color	white
Housing Material:	aluminum
Coating:	lacquered
Cover:	opal
Net Weight:	370 g
Type of Packaging:	box
Weight incl. Packaging:	0.37 kg
Warranty	3 years
Operating Hours:	50.000 h L70/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557812762

Information and Downloads:

