

Emergy HCE 10-740-1500lm WH



Product information "Emergy HCE 10-740-1500lm WH"

High Ceiling Emergency LED Luminaires

Our multipurpose stand-alone self-contained emergency high ceiling LED luminaires benefit from a sleek modern design and the high-end technology which is common to all of our products. With its high lumen output and low stand-by power consumption (< 0.5W) it can be used in either maintained or non-maintained applications. Designed to IP65 ingress protection and IK10 Impact protection requirements they are pre-wired and can be used in many indoor and outdoor lighting schemes.

The Advanced Self-Test (AST) technology built in as standard means it can be used either as part of a manual test (Key switch) lighting scheme or with the Advanced Remote Control (ARC) to add additional functionality. The High Ceiling Emergency Luminaire is manufactured in compliance with current standards including BS 60598-2-22.

The High Ceiling Emergency Luminaire can be mounted either on ceilings (both directly or suspended) or walls and comes with the corridor lens as standard however, it can be adapted for other environments with Accessory optional lenses.



Technical Details:

Luminous Flux	1500 lm
Light Yield:	150 lm/W
Light Temperature:	4000 K
Color Rendering Index (CRI)	≥70 Ra
Color Consistency (SDCM):	6
Power Consumption:	10 W
Operating Hours:	>50.000 h L70/B30
Switching Cycles:	>25.000
Ignition Time:	<1 s
Ambient Temperature (TA):	0°C - 40°C
Housing Material:	aluminum
Dimensions	200x200x58 mm
Net Weight:	2090 g
Warranty	5 years

Information and Downloads:

