

Emergy HCE PRO 10-840-1500lm SC DALI 2 WH



Product information "Emergy HCE PRO 10-840-1500lm SC DALI 2 WH"

LED escape route light with DALI 2 control

Emergency light with single battery supply for escape route lighting. 3 hours emergency lighting with Li-Ion battery 8000mAh, 6,4V. Good brightness and wide dispersion. LED light source with long life up to 50,000 hours. LED status display via green status LED. Nice, rectangular water- and dustproof IP65 body made of aluminum. Permanent phase monitoring. Emergency battery operation: 3 hours.

- Operating device: emergency / mains: electronic ballast
- Beam angle: symmetrical > 120 ° exchangeable lenses as option
- LED: 6W
- Luminous flux: typ. 1500 lumens
- Incl. pictogram with cutable directional arrow and person symbol
- Dimensions: see drawing
- viewing distance 20m

This is a self-test luminaire. Functional test is carried out automatically once a week and runs for 30 seconds. Full duration test is carried out automatically every 52 weeks. First full duration test is carried out automatically within the first 4 weeks after the luminaire being connected to mains voltage. This luminaire can be used in conjunction with the Advanced Remote Control (ARC). ARC is an optional tool that adds extra features to AST emergency luminaires. Please refer to the ARC's user guide

Technical Details:

Luminous Flux	1500 lm
Light Yield:	150 lm/W
Light Temperature:	4000 K
Color Rendering Index (CRI)	≥70 Ra
Color Consistency (SDCM):	6
Power Consumption:	10 W
Operating Hours:	>50.000 h L70/B30
Switching Cycles:	>25.000
Ignition Time:	<1 s
Ambient Temperature (TA):	0°C - 40°C
Housing Material:	aluminum
Warranty	5 years

Information and Downloads:

