

Emergy HCE PRO 10-840-1500lm SC DALI 2 WH



Technical Details:

Luminous Flux:	1500 lm
LED Output:	10 W
Light Yield:	150 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥70 Ra
Color Consistency (SDCM):	<6
Beam Angle:	120 °
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	DALI
Ignition Time:	<1 s
Input Current:	AC 220-240V, 50Hz
Power Consumption:	10 W
Contains Driver:	✓
Input Driver:	terminal
Switching Cycles:	>25.000
Ambient Temperature (TA):	0°C - 40°C
Storage Temperature:	0°C - 50°C

Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	65
IK Code:	08
Housing Material:	aluminum
Special Feature of Housing:	für bige Höhen
Cover:	Lens
Luminaire Type:	Fluchtwegleuchtung
Testing Facility:	programmierter Selbststest
Battery Warranty:	5
Discharge Duration:	≥5 h
Battery Type:	Li-Ion
Battery Current:	8000 mA
Battery Charge Duration:	8 h
Initial Charge Duration:	16 h
Charging Power Consumption:	12 W
Battery Cell Quantity	1
Luminous Flux in Battery Mode:	1500 lm
Standards for emergency luminaires:	DIN EN 60598-2-22, DIN EN 62034: 2012
Type of Packaging:	box
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L70/B30
Disposal Obligation:	✓

Information and Downloads:



Certifications	CE
<1W Stromaufnahme im Standby Modus	
< 1W power consumption in stand by	
DALI 2 steuerbar/control	
programmable central test via software	
exchangeable lens for different beamangles	