


# Alwetra 1500 30-47W-840-6700LM Wide Flood 1-10V Dim PWM



## Technical Details:

|                              |                      |
|------------------------------|----------------------|
| Luminous Flux:               | 6700 lm              |
| LED Output:                  | 45 W                 |
| Light Yield:                 | 143 lm/W             |
| Light Temperature:           | 4000 K               |
| Light Color:                 | neutralwhite         |
| Color Rendering Index:       | ≥80 Ra               |
| Color Consistency (SDCM):    | <4                   |
| Beam Angle:                  | 120 °                |
| Unified Glare Rating (UGR):  | <24                  |
| Light Emission:              | downward             |
| Dimmable:                    | ✓                    |
| Method of Dimming:           | 1-10V,PWM            |
| LED-Chip:                    | SMD 2835             |
| Ignition Time:               | <0,5 s               |
| Input Current:               | AC 220-240V, 50/60Hz |
| Power Consumption:           | 47 W                 |
| Contains Driver:             | ✓                    |
| Driver Manufacturer:         | Boke                 |
| Power Factor (PF):           | >0.95                |
| Input Driver:                | terminal             |
| CC/CV:                       | CC                   |
| Output Current Adjustable:   | ✓                    |
| Input Lamp:                  | plug connector       |
| Switching Cycles:            | >100.000             |
| Electrical Protection Class: | I                    |
| Ambient Temperature (TA):    | -20°C - 50°C         |
| Storage Temperature:         | -40°C - 60°C         |

|                                                 |                  |
|-------------------------------------------------|------------------|
| Mounting:                                       | ceiling,wall     |
| Montageart:                                     | surface mounted  |
| IP Class:                                       | 65               |
| IK Code:                                        | 10               |
| Housing Color                                   | white            |
| Housing Material:                               | Aluminium+PC     |
| Special Feature of Housing:                     | polycarbonate    |
| Cover:                                          | opal             |
| Net Weight:                                     | 2420 g           |
| Weight incl. Packaging:                         | 2.7 kg           |
| Content Master Package:                         | 6                |
| Dimensions of Master Package:                   | 1620x250x300 mm  |
| Weight Master Package:                          | 16,2 kg          |
| Product Line:                                   | Premio Line      |
| Warranty                                        | 5 years          |
| Operating Hours:                                | 50.000 h L80/B10 |
| Disposal Obligation:                            | ✓                |
| Customs Tariff Number:                          | 9405409990       |
| Certifications                                  | CE,LM80,D        |
| Barcode:                                        | 4250557815695    |
| Einfache, und schnelle Montage, In/Out          |                  |
| optionale Batterienotlichtmodule lieferbar      |                  |
| wählbare Ausgangsleistung: 30, 36, 40, 47W      |                  |
| dimmbare Version: 1-10V, Phasenwahl L1-L3       |                  |
| optional auch mediums Bewegungsmelder steuerbar |                  |

Information and Downloads:

