
Technical Data Sheet

**Order number: LG30651S**

# Xona Line 1280 32-840-4000LM Sensor








## Technical Details:

| | |
|---|---|
| **Luminous Flux:** | 4000 lm |
| **LED Output:** | 30 W |
| **Light Yield:** | 125 lm/W |
| **Light Temperature:** | 4000 K |
| **Light Color:** | neutralwhite |
| **Color Rendering Index:** | ≥80 Ra |
| **Color Consistency (SDCM):** | <3 |
| **Beam Angle:** | 120 ° |
| **Light Emission:** | downward |
| **LED-Chip:** | SMD 2835 |
| **Ignition Time:** | <0,5 s |
| **Input Current:** | AC 220-240V, 50/60Hz, DC 180-240V |
| **Power Consumption:** | 32 W |
| **Contains Driver:** | ✓ |
| **Power Factor (PF):** | >0.95 |
| **Input Driver:** | terminal |
| **CC/CV:** | CC |
| **Input Lamp:** | Terminal |
| **Switching Cycles:** | >100.000 |
| **Electrical Protection Class:** | II |
| **Compatible with Emergency Current:** | ✓ |
| **Ambient Temperature (TA):** | -20°C - 45°C |
| **Storage Temperature:** | -20°C - 55°C |

| | |
|---|---|
| **Dimensions:** | 1313x55x75 mm |
| **Mounting:** | ceiling,wall |
| **Montageart:** | surface mounted |
| **IP Class:** | 66 |
| **IK Code:** | 09 |
| **Housing Color** | hellgrey |
| **Housing Material:** | Polycarbonat |
| **Special Feature of Housing:** | drehbare Endkappe |
| **Cover:** | opal |
| **Net Weight:** | 1177 g |
| **Type of Packaging:** | box |
| **Dimensions of Packaging:** | 1390x90x90 |
| **Weight incl. Packaging:** | 1.572 kg |
| **Content Master Package:** | 10 |
| **Dimensions of Master Package:** | 1410x470x200 mm |
| **Weight Master Package:** | 16,1 kg |
| **Product Line:** | Advance Line |
| **Warranty** | 5 years |
| **Operating Hours:** | 50.000 h L80/B10 |
| **Disposal Obligation:** | ✓ |
| **Customs Tariff Number:** | 9405114090 |
| **Certifications** | CE,LM80,D |
| **Barcode:** | 4250557818863 |
| mit Bewegungsmelder | |
| with integrated motion sensor | |
| Vergleichbare Helligkeit: wie 2 x 36W T8 Röhre | |
| similar brightness as 2 x 36W T8 flourescent tube | |
| Master/Slave option | |

Information and Downloads:

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de