Technical Data Sheet

Order number: LG51220

BOKE PLL Serie







Technical Details:

Input Current:	AC 200 -240V, 350mA, 50/60Hz
Power Consumption:	30 W
Power Factor (PF):	>0.9
Input Driver:	terminal
Output of Driver:	DC 28-42V, 700mA
CC/CV:	CC
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 45°C

Dimensions:	131,9x45x30 mm
Montageart:	surface mounted
IP Class:	20
Housing Color	white
Housing Material:	plastic
Net Weight:	122 g
Type of Packaging:	box
Dimensions of Packaging:	170x52x43
Weight incl. Packaging:	0.145 kg
Content Master Package:	60
Dimensions of Master Package:	450x350x180 mm
Weight Master Package:	9,22 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	50.000 h
Disposal Obligation:	✓
Customs Tariff Number:	8504408390
Certifications	CE,TÜV,SELV,D
Barcode:	4250557816630

Information and Downloads:

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de