

# Kompakter Driver für Panel und Downlights



## Technical Details:

|                                    |                                             |
|------------------------------------|---------------------------------------------|
| Method of Dimming:                 | 1-10V                                       |
| Input Current:                     | AC 198-264V, 180mA, 50/60Hz,<br>DC 180-280V |
| Power Consumption:                 | 36 W                                        |
| Driver Manufacturer:               | KGP                                         |
| Power Factor (PF):                 | >0.92                                       |
| Input Driver:                      | terminal                                    |
| Output of Driver:                  | DC 10-50V, 150-900mA                        |
| CC/CV:                             | CC                                          |
| Output Current Adjustable:         | ✓                                           |
| Electrical Protection Class:       | II                                          |
| Compatible with Emergency Current: | ✓                                           |
| Ambient Temperature (TA):          | -20°C - 50°C                                |
| Storage Temperature:               | -20°C - 90°C                                |

|                                                   |                   |
|---------------------------------------------------|-------------------|
| Dimensions:                                       | 128x30x21 mm      |
| Montageart:                                       | recessed          |
| IP Class:                                         | 20                |
| Housing Color                                     | white             |
| Housing Material:                                 | plastic           |
| Special Feature of Housing:                       | ohne Zuentlastung |
| Net Weight:                                       | 119 g             |
| Weight incl. Packaging:                           | 0.125 kg          |
| Content Master Package:                           | 120               |
| Weight Master Package:                            | 12,56 kg          |
| Product Line:                                     | Advance Line      |
| Warranty                                          | 5 years           |
| Operating Hours:                                  | 50.000 h          |
| Certifications                                    | CE,ENEC,SELV      |
| Power Select: 320-1050mA, 50mA steps              |                   |
| perfect for LED panels and downlights             |                   |
| max. driver on 16A breaker: B Type: 21,C Type: 35 |                   |

Information and Downloads:

