

Lifud Dali to 0-10V Converter



Technical Details:

Dimmable:	✓
Method of Dimming:	DALI, Push-Dim
Input Current:	DC 11-13V
Power Consumption:	1 W
Driver Manufacturer:	Lifud
Input Driver:	terminal
Output of Driver:	DC 0-10V, 4mA
CC/CV:	CV
Output Current Adjustable:	✓
Switching Cycles:	>100.000
Electrical Protection Class:	III
Ambient Temperature (TA):	-20°C - 55°C
Storage Temperature:	-40°C - 60°C

Dimensions:	30x111 mm
Montageart:	surface mounted
IP Class:	67
Housing Color	white
Housing Material:	plastic
Net Weight:	70 g
Type of Packaging:	box
Weight incl. Packaging:	0.07 kg
Content Master Package:	90
Dimensions of Master Package:	400x330x140 mm
Weight Master Package:	6,8 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	25.000 h TC<60°C
Disposal Obligation:	✓
Customs Tariff Number:	8504408390
Certifications	CE, TÜV, SELV
Ideal Steuerung von 0-10V Komponenten über Dali	
Es wird ein 12V Netzteil benötigt!	
perfect controller from Dali to 0-10V max. 25mA	
an external powers supply 12V is needed	
10-100% (dim to off)	

Information and Downloads:

