

# Astrum Line MKIII Röhre 1500 25-830-4000LM



## Technical Details:

Luminous Flux:	3000 lm
Light Yield:	150 lm/W
Light Temperature:	4000 K
Light Color:	warmwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	140 °
Light Emission:	downward
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Input Current:	AC 100 - 240V, 50/60Hz
Power Consumption:	20 W
Contains Driver:	✓
Power Factor (PF):	>0.95
Output of Driver:	DC 70 - 75V, 40mA
CC/CV:	CC
Switching Cycles:	>200.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 45°C
Storage Temperature:	0°C - 35°C

Dimensions:	26x1512 mm
Length of Tube:	1500 mm
Socket:	G13
Rotating Socket:	✓
IP Class:	40
Housing Color	silver green
Housing Material:	aluminum
Special Feature of Housing:	Aluprofil inside
Cover:	frosted
Net Weight:	366 g
Type of Packaging:	box
Dimensions of Packaging:	35x35x1590
Weight incl. Packaging:	0.449 kg
Content Master Package:	36
Dimensions of Master Package:	1620x250x250 mm
Weight Master Package:	17,47 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	950540999
Certifications	CE,TÜV,LM79,LM80
Barcode:	4250557825731

Information and Downloads:

