Technical Data Sheet

Order number: LG56566

LITEGEAR® LED Lighting Solutions

Röhre XERIA ST ALU Prismatic Cover 1500-27-841-3150LM

Technical Details:

Luminous Flux:	3150 lm
LED Output:	27 W
Light Yield:	117 lm/W
Light Temperature:	4100 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<3
Beam Angle:	180 °
LED-Chip Manufacturer:	Epistar
LED-Chip:	SMD 2835
Ignition Time:	<1 s
Input Current:	AC 95 - 265V, 50/60Hz
Power Consumption:	27 W
Power Factor (PF):	>0.95
Switching Cycles:	>50.000
Ambient Temperature (TA):	-20°C - 45°C

Dimensions:	26x1500 mm
Length of Tube:	1500 mm
Socket:	G13
IP Class:	20
Cover:	clear
Net Weight:	405 g
Type of Packaging:	box
Weight incl. Packaging:	0.405 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	40.000 h L70/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE

Information and Downloads:

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de