

Emergency Brick Diffusor



Technical Details:

Light Emission:	
Ambient Temperature (TA):	0°C - 45°C
Storage Temperature:	-20°C - 55°C

Information and Downloads:



Mounting:	Decke
Montageart:	surface mounted
IP Class:	65
IK Code:	07
Housing Color	frosted
Housing Material:	plastic
Special Feature of Housing:	verwendbar mit LG60009
Cover:	opal
Net Weight:	410 g
Luminaire Type:	Rettungszeichenleuchte
Viewing Distance EN1838:	≥28 m
Sign Visible from Both Sides:	
Included Signs:	Pfeil links rechts oben unten
Standards for emergency luminaires:	Zeichen nach ISO 7010, Anforderung nach DIN EN 50172
Type of Packaging:	box
Dimensions of Packaging:	162x118x358
Weight incl. Packaging:	0.545 kg
Content Master Package:	6
Dimensions of Master Package:	525x375x275 mm
Weight Master Package:	4,0 kg
Product Line:	Essential Line
Warranty	2 years
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557817804
IP65 Aufsatz für LG60009	
wird anstelle der opt. Abdeckung verwendet	
macht aus Emergency Brick eine bidirektionale	

